

Page 1/11

Safety Data Sheet acc. to OSHA HCS

Printing date 01/30/2024

Reviewed on 01/30/2024

Tel.: +49 (0)800 4372522

1 Identification

- · Product identifier
 - · Trade name: Palavit 55 VS liquid

- · Application of the substance / the mixture Manufacture of dental prothesis
- · Details of the supplier of the safety data sheet
 - Manufacturer/Supplier:

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany)

Information department:

Tel. +1 (800) 431-1785 Fax: +1 (800) 522-1545 e-mail: customer.servicehkna@kulzer-dental.com

· Emergency telephone number:

Emergency CONTACT (24-Hour-Number)
ID 105860: (domestic) 1 800 535 5053 or international (001) 352 323 3500

2 Hazard(s) identification

Classification of the substance or mixture

H225 Highly flammable liquid and vapor. Flammable Liquids 2

Skin Irritation 2 H315 Causes skin irritation.

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure 3 H335 May cause respiratory irritation.

- · Label elements
 - GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:

methyl methacrylate

1.4-butandioldimethacrylate

Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

May cause an allergic skin reaction.

May cause respiratory irritation.

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Avoid breathing mist/vapours/spray.

Wear protective gloves / eye protection.

If skin irritation or rash occurs: Get medical advice/attention.

(Contd. on page 2)



Page 2/11

Safety Data Sheet acc. to OSHA HCS

Printing date 01/30/2024 Reviewed on 01/30/2024

Trade name: Palavit 55 VS liquid

(Contd. of page 1)

- · Additional information:
- 1 % of the mixture consists of component(s) of unknown toxicity.
- · Classification system
 - NFPA ratings for USA (scale 0-4)



Health = 2 Fire = 3 Reactivity = 2

HMIS-Ratings (Scale 0-4)



Health = 1 Fire = 3 Reactivity = 2

- · Results of PBT and vPvB assessment
 - · PBT: Not applicable.
 - · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
 - Description: Composition based on methacrylates

Dangerous components:				
	methyl methacrylate	>90%		
	Flammable Liquids 2, H225 Skin Irritation 2, H315; Sensitization - Skin 1, H317; Specific Target Organ Toxicity - Single Exposure 3, H335			
2082-81-7	1,4-butandioldimethacrylate	≥1-≤5%		
	Sensitization - Skin 1B, H317			

· Additional information For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- · Description of first aid measures
 - · After inhalation Supply fresh air; consult doctor in case of complaints.
 - · After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eve contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

Composition based on methacrylates

Information for doctor

· Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 3)



Page 3/11

Safety Data Sheet acc. to OSHA HCS

Printing date 01/30/2024 Reviewed on 01/30/2024

Trade name: Palavit 55 VS liquid

(Contd. of page 2)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
 - · Suitable extinguishing agents CO2, sand, extinguishing powder. Do not use water.
 - For safety reasons unsuitable extinguishing agents Water.
- · Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- · Advice for firefighters
 - · Protective equipment: No special measures required.
- · Additional information -

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Avoid contact with eyes and skin.
- · Environmental precautions: Prevent seepage into sewage system, workpits and cellars.
- Methods and material for containment and cleaning up:

Absorb with liquid binding material (diatomite, universal binders, for small amounts tissues).

Reference to other sections

No dangerous substances are released.

See Section 8 for information on personal protection equipment.

-

7 Handling and storage

- · Handling
 - · Precautions for safe handling Keep receptacles tightly sealed.
 - Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
 - ·Storage
 - Requirements to be met by storerooms and receptacles: Store in a cool location.
 - Information about storage in one common storage facility: Not required.
 - Further information about storage conditions:

Keep cool, if possible (not above 25 °C).

Store in cool, dry conditions in well sealed receptacles.

Specific end use(s) No further relevant information available.

US



Page 4/11

Safety Data Sheet acc. to OSHA HCS

Printing date 01/30/2024 Reviewed on 01/30/2024

Trade name: Palavit 55 VS liquid

(Contd. of page 3)

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
 - Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

80-62-6 methyl methacrylate

PEL Long-term value: 410 mg/m³, 100 ppm REL Long-term value: 410 mg/m³, 100 ppm

TLV Short-term value: 100 ppm Long-term value: 50 ppm

DSĚN, A4

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- Personal protective equipment
 - · General protective and hygienic measures

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

Not necessary with efficient local exhaust. If exposition to vapours is possible, use breathing protective mask (filter A).

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

If skin contact cannot be avoided, protective gloves are recommended to avoid possible sensitization.

Solvent resistant gloves

Check protective gloves prior to each use for their proper condition.

recommended

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR Nitrile rubber, NBR

(Contd. on page 5)



Page 5/11

Safety Data Sheet acc. to OSHA HCS

Printing date 01/30/2024 Reviewed on 01/30/2024

Trade name: Palavit 55 VS liquid

(Contd. of page 4)

· Eye protection: Safety glasses · Body protection: Light weight protective clothing

Information on basic physical and che	emical properties
General Information	
· Appearance:	Eluid
Form: Color:	Fluid Colorless
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Mixture is non-soluble (in water).
Change in condition	
· Melting point/Melting range:	-48 °C (-54.4 °F)
· Boiling point/Boiling range:	100 °C`(212 °F) [′]
· Flash point:	10 °C (50 °F)
· Flammability (solid, gaseous)	Not applicable.
· Auto igniting:	430.0 °C (806 °F)
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosivair/vapor mixtures are possible.
· Explosion limits:	
Lower:	2.1 Vol %
· Upper:	12.5 Vol %
· Vapor pressure at 20 °C (68 °F):	47 hPa (35.3 mm Hg)
· Density at 20 °C (68 °F):	0.940 g/cm³ (7.8443 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	4.0 "
· Water at 20 °C (68 °F):	1.6 g/l
· Partition coefficient (n-octanol/wate	er): Not determined.
· Viscosity:	
dynamic at 20 °C (68 °F):	1 mPas
kinematic:	Not determined.
Solvent content:	0.004
· Water:	0.2 %

(Contd. on page 6)



Page 6/11

Safety Data Sheet acc. to OSHA HCS

Printing date 01/30/2024 Reviewed on 01/30/2024

Trade name: Palavit 55 VS liquid

(Contd. of page 5)

· Other information

No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Possibility of hazardous reactions No dangerous reactions known
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- Hazardous decomposition products: none
- Additional information:

Product might polymerize after considerable exceeding of recommended storage time or temperature.

11 Toxicological information

- · Information on toxicological effects
 - · Acute toxicity:

· LD/	LC50 valu	es that are relevant for classification:	
80-62-6 m	ethyl met	hacrylate	
Oral	LD50	~7,900 mg/kg (rat)	
Dermal	LD50	>5,000 mg/kg (guinea pig) (OECD 402)	
Inhalative	LC50/4 h	29.8 mg/l (rat)	
2082-81-7	1,4-butan	dioldimethacrylate	
Oral	LD50	10,066 mg/kg (rat) (OECD 401)	
131-57-7 (Oxybenzo	ne	
Oral	LD50	>12,800 mg/kg (rat) (OECD 401)	
Dermal	LD50	>16,000 mg/kg (rabbit) (OECD 402)	
63393-96-	4 Quatern	ary ammonium compounds, tri-C8-10-alkylmethyl, chlorides	
Oral	LD50	200 mg/kg (ATE)	
		>200-<2,000 mg/kg (rat) (OECD 401)	

- · Primary irritant effect:
 - · on the skin: Irritant to skin and mucous membranes.
 - on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.

Additional toxicological information:
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
80-62-6 methyl methacrylate	3
· NTP (National Toxicology Program)	

None of the ingredients is listed.

(Contd. on page 7)



Page 7/11

Safety Data Sheet acc. to OSHA HCS

Printing date 01/30/2024 Reviewed on 01/30/2024

Trade name: Palavit 55 VS liquid

(Contd. of page 6)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

· Reproductive toxicity Based on available data, the classification criteria are not met.

12 Ecological information · Toxicity · Aquatic toxicity: 80-62-6 methyl methacrylate 49 mg/L (daphnia) (OECD 211) EC50/21d EC50/48h 69 mg/l (daphnia) (EPA OTS 797.1300) NOEC / 21d | 37 mg/l (daphnia) (OECD 211) ErC50 / 72 h >110 mg/l (algae) (OECD 201) NOEC / 72h | 110 mg/l (algae) (OECD 201) NOEC / 48h | 48 mg/l (daphnia) (EPA OTS 797.1300) EbC50 / 72h | >110 mg/l (algae) (OECD 201) NOEC/ 35d 9.4 mg/L (fish) (OECD 210) LC50/ 35d 33.7 mg/L (fish) (OECD 210) 2082-81-7 1,4-butandioldimethacrylate EC50/21d 14.1 mg/L (daphnia) (OECD 211) EC50/48h 32.5 mg/l (fish) NOEC / 21d | 5.09 mg/l (daphnia) (OECD 211) ErC50 / 72 h | 9.79 mg/l (algae) (OECD 201) NOEC / 72h | 2.11 mg/l (algae) (OECD 201) NOEC / 48h | 25 mg/l (fish) 4.35 mg/L (algae) (OECD 201) ErC10/72h 131-57-7 Oxybenzone 1.87 mg/l (daphnia) (OECD 202) EC50/48h LC50/96h 3.8 mg/l (fish) (OECD 203) ErC50 / 72 h | 0.67 mg/l (algae) (OECD 201) NOEC / 72h | 0.18 mg/l (algae) (OECD 201) NOEC / 96h | 0.72 mg/l (fish) (OECD 203) NOEC / 48h | 1.15 mg/l (daphnia) (OECD 202) 63393-96-4 Quaternary ammonium compounds, tri-C8-10-alkylmethyl, chlorides EC50/48h 0.16 mg/l (daphnia) (OECD 202) LC50/96h 0.15 mg/l (fish) (OECD 203) ErC50 / 72 h 0.29 mg/l (algae) (OECD 201) ErC10/72h 0.138 mg/L (algae) (OECD 201) (Contd. on page 8)

us.



Page 8/11

Safety Data Sheet acc. to OSHA HCS

Printing date 01/30/2024

Reviewed on 01/30/2024

Trade name: Palavit 55 VS liquid

(Contd. of page 7)

· Persistence and degradability

80-62-6 methyl methacrylate

biodegradability 94 % /14d (not defined) (OECD 301C)

2082-81-7 1,4-butandioldimethacrylate

biodegradability 84 % /28d (not defined) (OECD 310)

131-57-7 Oxybenzone

biodegradability 60-70 % /28d (not defined)

63393-96-4 Quaternary ammonium compounds, tri-C8-10-alkylmethyl, chlorides

biodegradability 10-<20 % /60d (not defined) (OECD 301B; ISO/ 9439/ EEC 92/69/V, C.4-C)

- · Behavior in environmental systems:
 - · Bioaccumulative potential

131-57-7 Oxybenzone

Bloconcentration factor (BCF) >33-<160 (fish) (OECD 305)

- **Mobility in soil** No further relevant information available.
- · Additional ecological information:
 - · General notes:

Do not allow product to reach ground water, water course or sewage system.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
 - · PBT: Not applicable.
 - vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
 - Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packagings:
 - Recommendation:

Disposal must be made according to official regulations.

Non contaminated packagings can be used for recycling.

14 Transport information

· UN-Number

· DOT, ADR, IMDG, IATA

UN1247

(Contd. on page 9)



Page 9/11

Safety Data Sheet acc. to OSHA HCS

Printing date 01/30/2024 Reviewed on 01/30/2024

Trade name: Palavit 55 VS liquid

(Contd. of page 8) UN proper shipping name DOT Methyl methacrylate monomer, stabilized solution 1247 METHYL METHACRYLATE MONOMER, · ADR STABILIZED solution · IMDG, IATA METHYL METHACRYLATE MONOMER, STABILIZED solution · Transport hazard class(es) · DOT · Class 3 Flammable liquids · Label · ADR ·Class 3 (F1) Flammable liquids · Label · IMDG, IATA · Class 3 Flammable liquids · Label · Packing group · DOT, ADR, IMDG, IATA II· Environmental hazards: · Marine pollutant: No · Special precautions for user Warning: Flammable liquids · Hazard identification number (Kemler code): 339 · EMS Number: F-E,S-D · Stowage Category · Stowage Code SW2 Clear of living quarters. · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information:

(Contd. on page 10)



Page 10/11

Safety Data Sheet acc. to OSHA HCS

Printing date 01/30/2024 Reviewed on 01/30/2024

Trade name: Palavit 55 VS liquid

(Contd. of page 9)

· ADR

· Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500

ml

1L

· IMDG

· Limited quantities (LQ)

· Excepted quantities (ÉQ) Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500

ml

· UN "Model Regulation": UN 1247 METHYL METHACRYLATE MONOMER,

STABILIZED SOLUTION, 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

SARA Section 355 (extremely hazardous substances)

None of the ingredients is listed.

· SARA Section 313 (specific toxic chemical listings)

80-62-6 methyl methacrylate

Proposition 65

Prop 65 - Chemicals known to cause cancer

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

80-62-6 methyl methacrylate

E;NL

TLV (Threshold Limit Value)

80-62-6 methyl methacrylate

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

(Contd. on page 11)



Page 11/11

Safety Data Sheet acc. to OSHA HCS

Printing date 01/30/2024 Reviewed on 01/30/2024

Trade name: Palavit 55 VS liquid

(Contd. of page 10)

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

Date of preparation / last revision 01/30/2024

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit

PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Flammable Liquids 2: Flammable liquids – Category 2
Skin Irritation 2: Skin corrosion/irritation – Category 2
Sensitization - Skin 1: Skin sensitisation – Category 1
Sensitization - Skin 1B: Skin sensitisation – Category 1B
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.