

Page 1/8

## Safety Data Sheet according to HPR, Schedule 1

Printing date 08/05/2020

Reviewed on 08/05/2020

Tel.: +49 (0)800 4372522

#### 1 Identification

- · Product identifier
  - · Trade name: Signum zirconia bond I
    - · Application of the substance / the mixture Zirconia-Resin Bonding System
- · Details of the supplier of the safety data sheet
  - Manufacturer/Supplier:

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany)

· Information department:

Tel. +1 (800) 431-1785 Fax: +1 (800) 522-1545 e-mail: customer.servicehkna@kulzer-dental.com

· Emergency telephone number:

Emergency CONTACT (24-Hour-Number)
ID 105860: (domestic) 1 800 535 5053 or international (001) 352 323 3500

## 2 Hazard identification

· Classification of the substance or mixture

Flammable Liquids - Category 2 H225 Highly flammable liquid and vapour. Eye Irritation - Category 2A H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure - H336 May cause drowsiness or dizziness. Category 3

- · Label elements
  - GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labeling: acetone
- · Hazard statements

Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wear protective gloves / eye protection.

If eye irritation persists: Get medical advice/attention.

Classification system

NFPA ratings for USA (scale 0-4)



Health = 2Fire = 3Reactivity = 0

(Contd. on page 2)



Page 2/8

(Contd. of page 1)

## Safety Data Sheet according to HPR, Schedule 1

Printing date 08/05/2020

Reviewed on 08/05/2020

## Trade name: Signum zirconia bond I

· HMIS-Ratings (Scale 0-4)

3 REACTIVITY 0 Reactivity = 0

Health = 2Fire = 3

· Other hazards -

## 3 Composition/Information on ingredients

- · Chemical characterization: Mixtures
  - Description: -

· Dangero	us components:	
67-64-1	acetone Flammable Liquids - Category 2, H225 Eye Irritation - Category 2A, H319; Specific Target Organ Toxicity - Single Exposure - Category 3, H336	>90% w/w
85590-00-7	7 10-Methacryl-oxydecyl-dihydrogenphosphat Skin Irritation - Category 2, H315; Eye Irritation - Category 2A, H319; Specific Target Organ Toxicity - Single Exposure - Category 3, H335	
64-19-7	acetic acid Flammable Liquids - Category 3, H226 Corrosive to Metals - Category 1, H290; Skin Corrosion - Category 1A, H314 Specific concentration limits: Skin Corrosion - Category 1A; H314: C ≥ 90 % Skin Corrosion - Category 1B; H314: 25 % ≤ C < 90 % Skin Irritation - Category 2; H315: 10 % ≤ C < 25 % Eye Irritation - Category 2; H319: 10 % ≤ C < 25 %	0-5% w/w *

<sup>\*</sup> Actual concentration ranges are withheld as a trade secret.

## 4 First-aid measures

- · Description of first aid measures
  - After inhalation Supply fresh air; consult doctor in case of complaints.
  - After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

Information for doctor

· Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

<sup>·</sup> Additional information For the wording of the listed hazard phrases refer to section 16.



Page 3/8

## Safety Data Sheet according to HPR, Schedule 1

Printing date 08/05/2020

Reviewed on 08/05/2020

## Trade name: Signum zirconia bond I

(Contd. of page 2)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

## 5 Fire-fighting measures

- Extinguishing media
  - · Suitable extinguishing agents

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents Water with full jet.
- · Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- · Advice for firefighters
  - · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information -

## 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Avoid contact with eyes and skin.

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Prevent seepage into sewage system, workpits and cellars.
- Methods and material for containment and cleaning up:

Absorb with liquid binding material (diatomite, universal binders, for small amounts tissues). Ensure adequate ventilation.

Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 13 for disposal information.

See Section 8 for information on personal protection equipment.

## 7 Handling and storage

- · Handling
  - Precautions for safe handling

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
  - · Storage
    - Requirements to be met by storerooms and receptacles: Store in a cool location.
    - Information about storage in one common storage facility: Not required.
    - Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

CDN



Page 4/8

# Safety Data Sheet according to HPR, Schedule 1

Printing date 08/05/2020 Reviewed on 08/05/2020

Trade name: Signum zirconia bond I

(Contd. of page 3)

## 8 Exposure controls/ Personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
  - · Components with limit values that require monitoring at the workplace:

#### 67-64-1 acetone

EL () Short-term value: 500 ppm Long-term value: 250 ppm

EV () Short-term value: 750 ppm Long-term value: 500 ppm

#### 64-19-7 acetic acid

EL () Short-term value: 15 ppm Long-term value: 10 ppm

EV () Short-term value: 37 mg/m³, 15 ppm Long-term value: 25 mg/m³, 10 ppm

· Additional information: The lists that were valid during the creation were used as basis.

#### · Exposure controls

### Personal protective equipment

#### General protective and hygienic measures

Avoid contact with the eyes.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

#### · Breathing equipment:

Not necessary with efficient local exhaust. If exposition to vapours is possible, use breathing protective mask (filter A).

#### Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Check protective gloves prior to each use for their proper condition.

recommended

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR Nitrile rubber, NBR

- · Eye protection: Tightly sealed goggles.
- · Body protection: Protective work clothing.

CDN



Page 5/8

# Safety Data Sheet according to HPR, Schedule 1

Printing date 08/05/2020 Reviewed on 08/05/2020

Trade name: Signum zirconia bond I

(Contd. of page 4)

	ies
Information on basic physical and ch	emical properties
General Information	
Appearance: Form:	Fluid
· Color:	Colorless
· Odor:	Acetone-like
Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	undetermined
Boiling point/Boiling range:	55 °C (131 °F)
· Flash point:	-19 °C (-2.2 °F)
· Flammability (solid, gaseous)	Not applicable.
· Ignition temperature:	465 °C (869 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation explosive air/vapor mixtures are possible.
· Explosion limits:	
·Lower:	2.6 Vol %
· Upper:	13.0 Vol %
· Vapor pressure at 20 °C (68 °F):	247 hPa (185.3 mm Hg)
· Density:	Not determined
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· Water:	Not miscible or difficult to mix
· Partition coefficient (n-octanol/wa	ter): Not determined.
· Viscosity:	
dynamic:	Not determined.
· kinematic:	Not determined.
· Other information	No further relevant information available.

## 10 Stability and reactivity

- Reactivity No further relevant information available.
  Possibility of hazardous reactions No dangerous reactions known
  Conditions to avoid No further relevant information available.
  Incompatible materials: No further relevant information available.
  Hazardous decomposition products: none

- · Additional information: -



Page 6/8

## Safety Data Sheet according to HPR, Schedule 1

Printing date 08/05/2020

Reviewed on 08/05/2020

## Trade name: Signum zirconia bond I

(Contd. of page 5)

## 11 Toxicological information

- Information on toxicological effects
  - · Acute toxicity:

· LD/LC50 values that are relevant for classification:						
67-64-1 acetone						
Oral	LD50	5,800 mg/kg (rat)				
Dermal	LD50	>15,700 mg/kg (rabbit) weight of evidence				
Inhalative	LC50/4 h	76 mg/l (rat) weight of evidence				
64-19-7 acetic acid						
Oral	LD50	3,310 mg/kg (rat) weight of evidence				
Inhalative	LC50/4 h	11.4 mg/l (rat) (OECD 403) weight of evidence				

- · Primary irritant effect:
  - on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- Subacute to chronic toxicity:

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the

- · Additional toxicological information: Irritant
  - · Carcinogenic categories

IARC (International Agency for Research on Can
--

128-37-0 Butylated hydroxytoluene

3

· NTP (National Toxicology Program)

None of the ingredients is listed.

## 12 Ecological information

- · Toxicity
  - · Aquatic toxicity:

#### 67-64-1 acetone

EC50/48h 6,100 mg/l (daphnia)

LC50/96h 5,540 mg/l (fish)

#### 64-19-7 acetic acid

EC50/48h >300.82 mg/l (daphnia)

LC50/96h 1,000 mg/l (fish)

- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
  · Bioaccumulative potential No further relevant information available.
  - Mobility in soil No further relevant information available.
- · Results of PBT and vPvB assessment
  - · PBT: Not applicable.
  - · vPvB: Not applicable.

(Contd. on page 7)



Page 7/8

# Safety Data Sheet according to HPR, Schedule 1

Printing date 08/05/2020

Reviewed on 08/05/2020

## Trade name: Signum zirconia bond I

· Other adverse effects No further relevant information available.

(Contd. of page 6)

## 13 Disposal considerations

- · Waste treatment methods
  - · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packagings:
  - · Recommendation:

Disposal must be made according to official regulations. Non contaminated packagings can be used for recycling.

14 Transport i	information
----------------	-------------

· UN-Number

• **DOT/TDG** UN1090 • **ADR, IMDG, IATA** 1090

· UN proper shipping name

· ADR 1090 ACETONE, solution ACETONE, solution

- · Transport hazard class(es)
  - · DOT/TDG (Transport dangerous goods):



· Class 3 Flammable liquids

Label

· ADR



· Class 3 (F1) Flammable liquids

·Label

· IMDG, IATA



· Class 3 Flammable liquids

· Label

· Packing group

· DOŤ/ŤDG, ADR, IMDG, IATA //

(Contd. on page 8)



Page 8/8

## Safety Data Sheet according to HPR, Schedule 1

Printing date 08/05/2020 Reviewed on 08/05/2020

## Trade name: Signum zirconia bond I

(Contd. of page 7)

· Environmental hazards:

Marine pollutant:

No

· Special precautions for user

Warning: Flammable liquids

· Hazard identification number (Kemler

code):

· EMS Number:

F-E,S-D

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code

Not applicable.

· Transport/Additional information:

UN "Model Regulation":

UN1090, Acetone, solution, 3, II

## 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
  - SARA Section 355 (extremely hazardous substances)

None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

· Date of the latest revision of the safety data sheet 08/05/2020 / 3

Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

\* Data compared to the previous version altered.